

Vierkantrohre



b in mm	s in mm	Abmessungen in mm	kg/mtr.	EN AW-6060 T66 Al Mg Si 0,5 F22	EN AW-6082 T6 Al Mg Si 1 F28
15	2	15 x 15 x 2	0.29	x o	
15	1.5	15 x 15 x 1,5	0.22	o	
20	3	20 x 20 x 3	0.56	o	
20	2	20 x 20 x 2	0.39	x o	
20	1.5	20 x 20 x 1,5	0.31	o	
25	1.5	25 x 25 x 1,5	0.39	o	
25	2	25 x 25 x 2	0.52	x o	
25	3	25 x 25 x 3	0.72	x o	
30	2	30 x 30 x 2	0.61	x o	
30	3	30 x 30 x 3	0.88	x o	
34	3	34 x 34 x 3	1.02	x o	
34	2	34 x 34 x 2	0.70	o	
35	2	35 x 35 x 2	0.73	x o	
35	3	35 x 35 x 3	1.06	o	
40	2	40 x 40 x 2	0.84	x o	
40	3	40 x 40 x 3	1.22	x o	
40	2.5	40 x 40 x 2,5	1.03	x o	
40	4	40 x 40 x 4*	1.58		x
40	4	40 x 40 x 4	1.56	x o	
45	2	45 x 45 x 2	0.95	o	
50	4	50 x 50 x 4	2.02	x o	
50	3	50 x 50 x 3	1.55	x o	
50	2	50 x 50 x 2	1.06	x o	
50	5	50 x 50 x 5	2.48	o	
50	2.5	50 x 50 x 2,5	1.31	o	
55	2	55 x 55 x 2	1.17	x	
60	4	60 x 60 x 4	2.46	x o	x
60	3	60 x 60 x 3	1.88	x o	
60	2	60 x 60 x 2	1.28	o	
70	2	70 x 70 x 2	1.50	o	
70	4	70 x 70 x 4	2.90	x o	
80	5	80 x 80 x 5	4.18	x o	
80	6	80 x 80 x 6	4.88	o	x
80	8	80 x 80 x 8**	6.37		x
80	3	80 x 80 x 3	2.54	x o	
80	4	80 x 80 x 4	3.34	x o	
80	2	80 x 80 x 2	1.72	o	
90	4	90 x 90 x 4	3.78	x o	
100	2	100 x 100 x 2	2.16	x o	
100	5	100 x 100 x 5**	5.22	x o	x
100	4	100 x 100 x 4	4.22	x o	
100	3	100 x 100 x 3	3.20	o	
120	5	120 x 120 x 5**	6.33	o	x
125	6	125 x 125 x 6	7.85		x
150	5	150 x 150 x 5**	7.98	o	x

x = Lager Bremen, o = Lager Dortmund

Stand: 08.08.2018